# **XM200G SERIES**

## PERFORMANCE METAL 3D PRINTING AT AN AFFORDABLE PRICE



## A HIGHLY CONFIGURABLE COMBINATION OF INDUSTRIAL SPEED & PERFORMANCE AT AN AFFORDABLE PRICE

Xact Metal 3D printers combine the critical additive manufacturing specifications of metal powder-bed fusion (SLM/DMLS) with cutting-edge technology to offer uncompromised as-printed part quality at an affordable price.

The XM200G printer series meets the specification demands of high-performance use cases in manufacturing, research & development and other applications where print speed, part quality, and affordable price is essential.

### **XM200G FEATURES**

- Single or dual<sup>5</sup> 100, 200 or 400W fiber laser option
- Overlapping dual-laser work-areas
   100% with a 100 µm spot size
  - 66% using a 50 µm spot size
- High-speed galvanometer with standard, performing or watercooled option
- Premium F-theta lens for micron consistency across scan field
- Optional spot sizes
   50 µm or 100 µm
- Large build volume
- Small footprint
- Modern software architecture
- Open material and open parameters
- Integrated powder handling

#### **TECHNICAL SPECS**

Build Volume <sup>4</sup>	150 x 150 x 150 mm or 125 x 125 x125 mm
Laser Type <sup>1</sup>	<ul> <li>XM200G - Single 100W, 200W, or 400W Yb fiber laser</li> <li>XM200G2 - Dual 100W, 200W, or 400W Yb fiber lasers</li> </ul>
Build Speed	<ul> <li>XM200G - ~6 to 9 cc/hr</li> <li>XM200G2 - ~12 to 16 cc/hr</li> </ul>
Jogging Speed	Up to 20.7 m/sec (Standard galvo), 34.6 m/sec (Performance galvo)
Precision Optics Spot Size	Approximately 50 or 100 µm
Layer Thickness	20 up to 100 µm
Glovebox	Available
User Interface	21" intuitive user-friendly touch screen
Electrical <sup>2</sup>	Power Supply 100-120/200-240 VAC Single Phase, 50/60 Hz 1.5 kW, 2.0 kW Peak
Exterior Dimensions	650 x 780 x 1,930 mm³ - W x D x H (25.6 x 30.7 x 76 in³)
Weight	<ul> <li>XM200G - ~380 kgs (~840 lbs)</li> <li>XM200G2 - ~425 kgs (~940 lbs)</li> </ul>
Powder Options <sup>3</sup>	<ul> <li>Aluminum Si10Mg</li> <li>Bronze, Copper (C18150)</li> <li>Stainless Steel: 316L, 17-4 PH, 15-5, 400 Series</li> <li>Super Alloys: 718, 625, Cobalt Chrome F75, Hastelloy<sup>®</sup> X,</li> <li>Titanium Ti64</li> <li>Tooling Steels: Maraging M300</li> </ul>

Xact Metal and Xact Core are trademarks of Xact Metal, Inc.

- 1. Class 1 Laser Product, 2. Not all configurations available on 120 volts.
- 3. Availability of parameters available on request, 4. Using standard build plate 5. With dual laser, limited to one laser per part. Dual laser per part to be

released in 2025.

