

XM200G SERIES

PERFORMANCE METAL 3D PRINTING
AT AN AFFORDABLE PRICE



A HIGHLY CONFIGURABLE COMBINATION OF INDUSTRIAL SPEED & PERFORMANCE AT AN AFFORDABLE PRICE

Xact Metal 3D printers combine the critical additive manufacturing specifications of metal powder-bed fusion (SLM/DMLS) with cutting-edge technology to offer uncompromised as-printed part quality at an affordable price.

The XM200G printer series meets the specification demands of high-performance applications in manufacturing, research & development and other uses where print speed, part quality, and affordable price are essential.

XM200G FEATURES

- Single or dual⁵ 100, 200 or 400W fiber laser option
- 100% overlapping dual-laser work-areas
- High-speed galvanometer with standard, performing or water-cooled option
- Premium F-theta lens for micron consistency across scan field
- Optional spot sizes - 50 µm or 100 µm
- Large build volume
- Small footprint
- Modern software architecture
- Open material and open parameters
- Integrated powder handling

TECHNICAL SPECS

| | |
|-----------------------------------|---|
| Build Volume⁴ | 150 x 150 x 150 mm or 125 x 125 x 125 mm |
| Laser Type¹ | <ul style="list-style-type: none"> • XM200G - Single 100W, 200W, or 400W Yb fiber laser • XM200G2 - Dual 100W, 200W, or 400W Yb fiber lasers |
| Build Speed | <ul style="list-style-type: none"> • XM200G - ~6 to 9 cc/hr • XM200G2 - ~12 to 16 cc/hr |
| Jogging Speed | Up to 20.7 m/sec (Standard galvo), 34.6 m/sec (Performance galvo) |
| Precision Optics Spot Size | Approximately 50 or 100 µm |
| Layer Thickness | 20 up to 100 µm |
| Glovebox | Available |
| User Interface | 21" intuitive user-friendly touch screen |
| Electrical² | Power Supply 100-120/200-240 VAC Single Phase, 50/60 Hz 1.5 kW, 2.0 kW Peak |
| Exterior Dimensions | 650 x 780 x 1,930 mm ³ - W x D x H (25.6 x 30.7 x 76 in ³) |
| Weight | <ul style="list-style-type: none"> • XM200G - ~380 kgs (~840 lbs) • XM200G2 - ~425 kgs (~940 lbs) |
| Powder Options³ | <ul style="list-style-type: none"> • Aluminum Si10Mg • Bronze, Copper (C18150) • Stainless Steel: 316L, 17-4 PH, 15-5, 400 Series • Super Alloys: 718, 625, Cobalt Chrome F75, Hastelloy[®] X, • Titanium Ti64 • Tooling Steels: Maraging M300 |

Xact Metal and Xact Core are trademarks of Xact Metal, Inc.

1. Class 1 Laser Product, 2. Not all configurations available on 120 volts.
3. Availability of parameters available on request, 4. Using standard build plate
5. With dual laser, limited to one laser per part. Dual laser per part to be released in 2025.

