

# 20% Cycle Time Reduction By using Innovated Sprinkler Head Mold Insert

#### **CHALLENGE**

K-Rain aimed to boost productivity by cutting cycle times. Their first attempt using stainless steel with conventional cooling methods with cooling rods was found to be ineffective

#### SOLUTION

Partnering with Zero Tolerance LLC, they switched to Xact Metal's 3D printing technology and Uddeholm's Corrax® — a corrosion-resistant tool steel — delivering durable inserts and lasting performance.






### SPRINKLER HEAD MOLD INSERT WITH CONFORMAL COOLING - PROCESS

Simulation in Moldex3d software run by Reaction Plastics Solutions. Design done in Cimatron.


#### **SOFTWARE SIMULATION**



#### **CAD MODEL DESIGN**

Conformal cooling designed in Cimatron software saves a minimum 5 seconds in cycle time.

#### SIDE BY SIDE VIEW OF CAVITY SURFACE TEMPERATURE AT END OF CYCLE.



#### 35 HRS. PRINT TIME!



AS PRINTED 35 hrs. (quantity: 4)

Printed in Uddeholm Corrax Steel.

#### 50 HRC AND A2 POLISH



FINISH MACHINING (after heat treatment)

Zero Tolerance was able to heat treat the mold inserts up to 50 HRC, machine, EDM and then polish to an A2 surface finish.

## SPRINKLER HEAD MOLD INSERT WITH CONFORMAL COOLING - FINAL INSERT






## SPRINKLER HEAD MOLD INSERT WITH CONFORMAL COOLING - RESULTS





### REDUCED CYCLE TIME BY 20%

Reduced cycle time from 52 to 49sec. with a faster hydraulic unscrewing motor then from 49 to 41 sec. with new designed insert with conformal cooling circuit. This design change also almost completely eliminated sink on surface of the part.





K Rain plans to continue modifying multi production molds by printing with Xact Metal technology in Uddeholm Corrax Steel through Zero Tolerance CNC.

#### JOINT VENTURE \_\_\_\_\_



K-Rain, one of the world's largest manufacturers of irrigation products



Uddeholm's Corrax® additive powder



Zero Tolerance LLC, a leading mold builder based in Michigan



Xact Metal's affordable 3D printing technology





